				SAFE	ETY D	AT	4 5	SH	EE	Т				-	1 of 6 -093
Prepa	red to OSHA, ACC,	ANSI, NOF	ISC, WHMIS, 20	001/58 & 1272/20	008/EC Standard	ls		SDS	Revision	n: 1.2		SDS R	levision	Date: 6/10	0/2019
			1. 1	PRODUC		PANY	IDF			TION					
1.1	Product Name:	C													
1.2	Chemical Name:		Urethane blend												
1.3	Synonyms:	-	860540, 860550, 860551												
1.4	Trade Names:		earlok [®] EXT	,											
1.5	Product Use:	Se	ealant												
1.6	Distributor's Name:	Bi	rchwood Labo	oratories LLC											
1.7	Distributor's Address:	79	000 Fuller Roa	d, Eden Prairie	e, MN 55344 U	SA									
1.8	Emergency Phone:	С	hemTrec +1	(800) 424-93	300 / +1 (703) 527-38	87 or	Poiso	on Cor	ntrol C	ente	e <mark>r</mark> +1 (855) 2	81-1742	2
1.9	Business Phone / Fax:	+	1 (952) 937-7	900 / +1 (952)	937-7979										
				2. HA	ZARDS I	DENT	FIC		DN						
2.1	Hazard Identification:	[N D/ DI	IOHSC: 1088 ANGER! HIG ROWSINESS	classified as a (2004)] and AE GHLY FLAMM OR DIZZINES lam. Liq. 2, Ski	hazardous su OG Code (Aust ABLE LIQUI S. CAUSES S	bstance b ralia). D AND \ SKIN IRRI	ut not /APOR TATIO	as dar R. CA N.	ngerous						
 Label Elements: Hazard Statements (H): H225 – Highly flammable liquid and vapor. H319 – Causes serious et irritation. H336 – May cause drowsiness or dizziness. H315 – Causes skin irritation. Precautionary Statements (P): P210 – Keep away from heat, hot surfaces, sparks, open flames a other ignition sources. No smoking. P233 – Keep container tightly closed. P240 – Ground a bond container and receiving equipment. P241 – Use explosion proof equipment. P242 – Use not sparking tools. P243 – Take action to prevent static discharges. P262 - Do not get in eyes, on sk or on clothing. P261 – Avoid breathing dust/fume/mist/vapor/spray. P264 - Wash skin thoroug after handling. P270 - Do not eat, drink or smoke when using this product. P271 – Use o outdoors or in a well-ventilated area. P280 - Wear protective gloves/eyewear/protective clothin P302+P352 - IF ON SKIN: Gently wash with plenty of soap and water. P321 - Specific treatmer see supplemental first aid instructions in section 4 of this Safety Data Sheet). P362+p364 – Take contaminated clothing and wash it before reuse. P303+P361+P353 – IF ON SKIN (or hair): Take immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 – INHALED: Remove person to fresh air and keep comfortable for breathing. P312 – Call a POISC CENTER/doctor if you feel unwell. P305+P351+P338 – IF IN EYES: Rinse cautiously with water several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P3 – If eye irritation persists: Get medical advice/attention. P370+P378 – In case of fire: Use C0 Halon (if permitted), Dry Chemical, Foam, as authorized to extinguish. P403+P235 – Store in a w ventilated place. Keep cool. P405 – Store locked up. P501 - Dispose of contents/ container to ventilated place. 				thes and se non- on skin roughly se only lothing thent Take of Γ ake of Γ ake of Γ ake of Γ ake of Γ ake of Γ ake of Γ ake of Γ ake of Γ	d d - - y y y - - ff ff ff - N r 3 3										
2.3	Other Warnings:	4	State of to www.P	G: This product California to 65Warnings.ca JT OF REACH	cause cance a.gov.	r, birth c	lefects	or o	ther re	produc	tive	harm.	For	more inf	formation, go
			3 60	MPOSITI			FNT	INF		ΙΔΤΙά	N				
			0.00						U 1 1 1			MITS IN	AIR (ma	/m³)	
							AC	GIH	I	NOHSC			OSH.		
							pp	m		ppm			ppm	1	_
СНЕМІ	CAL NAME(S)		CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL F	ES- PEAK	TLV	STEL	IDLH	OTHER
			141-78-6	AH5425000	205-500-4	40-50	400	400	200		NF	NA	NA	2000	400 TWA
C1111				ye Irrit. 2; STOT			NIA	NA				NIA	NIA	NIA	
ETHYL 3-ETHOXYPROPIONATE		NATE	763-69-9	UF3325000	212-112-9 F	10-50 lam. Lig. 3:	NA Aquati	NA c Chror	NF nic 3; H2		NF 2	NA	NA	NA	
XYLENE			1330-20-7	ZE2100000	215-535-7	5-10	100	150	(80)	350	NF	100	150	900	
				cute Tox. Oral 4,								200	200	500	SKIN
TOLUENE			108-88-3 Flam, Lig, 2: A	XS52500000 sp. Tox. 1; Skin I	203-625-9 rrit. 2: STOT SE	5-10 3: Repr.2:	50 STOT F	300 RE 2: H	100 1225. H3		574 5. H33	200 36	300	500	SKIN
N-BUTYL ALCOHOL			71-36-3	EO1400000	200-751-6	5-10	NA	50	(50)	152	50	100	NA	NA	
				cute Tox. 4 *; ST		1			SÈ 3; H2						
ACETONE (2-PROPANONE)		E)	67-64-1 Flam Lig 2: F	AL3150000 ye Irrit. 2; STOT :	200-662-2 SE 3 H225 H31	1-5 9 H336	1800	NA	1185	2375	NF	2400	NA	2500	
	TONE ALCOHOL		123-42-2	SA9100000	NA	1-5	50	240	238	NF	NF	20	240	1800	
		(0.0)	Eye Irrit. 2; H3 64-17-5	19 KQ6300000	200-578-6	0.1-1	1000	3000	1000	1800	NF	1000	1900	3300	
EIHA	NOL (SD ALCOHOL	40B)	Flam. Liq. 2; H	225											
CYCL	OHEXANONE		108-94-1 Flam. Liq. 3; A	GW1050000 cute Tox. 4 *; H2	203-631-1 26, H332	0.1-1	25	50	(25)	100	NA	50	NA	700	

Γ

Page 2 of 6 BTI-093

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.2 SDS Revision Date: 6/10/2019 4. FIRST AID MEASURES First Aid: DO NOT INDUCE VOMITING. Contact ChemTrec +1 (800) 424-9300 or the nearest Poison Control 4.1 Ingestion: Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, Eyes: holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. Skin: Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned. Inhalation: Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention. 4.2 Effects of Exposure: If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, Eyes: irritation and watering May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, Inhalation: nose and respiratory tract. 4.3 Symptoms of Overexposure: If product is swallowed, may cause gastrointestinal disturbance. Ingestion: Eyes: Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 4.4 Acute Health Effects: Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Chronic Health Effects: 4.5 Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals. 4.6 Target Organs: Eyes, Skin. Medical Conditions 4.7 Pre-existing dermatitis, other skin conditions. 2 HEALTH Aggravated by Exposure: FLAMMABILITY 3 PHYSICAL HAZARDS 1 **PROTECTIVE EQUIPMENT** I EYES SKIN LUNGS 4.8 Notes to Physician: Symptoms of poisoning may even occur after several hours; therefore, medical observation for at least 48 hours after the accident. 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: 5.1 WARNING! FLAMMABLE LIQUID AND VAPOR! Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Extinguishing Methods: 5.2 CO2, Halon (if permitted), Dry Chemical, Foam, as authorized. 5.3 Firefighting Procedures: This product is a Class IIIB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). Use safety glasses or safety goggles and face shield; use gloves and other protective clothing (e.g., apron, boots, etc.) to prevent skin contact. Small Spills: Wear appropriate protective equipment including gloves and protective evewear. Use a non-combustible, inert material such as vermiculite or sand to soak up the product and place into a container for later disposal. Large Spills: Keep incompatible materials (e.g., strong acids, alkalis, oxidizers) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Recover as much free liquid as possible and collect in acid-resistant container. Use absorbent to pick up residue. Avoid discharging liquid directly into a sewer or surface waters.

		SAFE	TY	DA	TA S	SHE	ET				Page 3 of 6 BTI-093
repa	ared to OSHA, ACC, ANSI, I	NOHSC, WHMIS, 2001/58 & 1272/200	8/EC Stand	lards		SDS Re	vision: 1.2		SDS Rev	vision Da	te: 6/10/2019
	1	7. HANDLIN									
.1	Work & Hygiene Practices:	Avoid breathing mists or spray. Avoid eye and skin contact. Wear protective equipment when handling product. Keep out of the reach of children. Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Do not expose to heat and flame. Use only in ventilated areas. Immediately clean-up and decontaminate any spills or residues.									
.2	Storage & Handling:	KEEP OUT OF THE REACH OF CHILDREN. Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Keep containers covered when not in use. Store at temperatures at or below 25 °C (77 °F). Keep away from incompatible substances (see Section 10). Protect containers from physical damage.									
.3	Special Precautions:	Empty containers may retain haz	,			is nom pri	ysical dam	age.			
		8. EXPOSURE CON	ITROL	S &	PERSC)NAL F	PROTE	CTIC)N		
.1	Exposure Limits:		AC	GIH		NOHSC	T		OSHA	T	OTHER
	ppm (mg/m ³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
			400	400	200 (80)	400	NF NF	NA 100	NA 150	2000	400 TWA
		XYLENE TOLUENE	50	150 300	100	350 150	574	100 200	300	900 500	SKIN
		N-BUTYL ALCOHOL	NA	50	(50)	152	50	100	NA	NA	
		ACETONE	1800	NA	1185	2375	NF	2400	NA	2500	
		DIACETONE ALCOHOL	50	240	238	NF	NF	20	240	1800	
		ETHANOL (SD ALCOHOL 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
.2	Ventilation & Engineering		25	50	(25)	100	NA NA	50	NA	700	generated from t
.2	Controls:	Use local or general exhaust ve handling of this product. Ensure station).									
.3	Respiratory Protection:	In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.									
.4	Eye Protection:	Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended.									
8.5	Hand Protection:	Wear protective, chemical-resist	ant gloves	s (e.g., ı	neoprene)	when usir	ng or handl	ing this	product	t.	
8.6	Body Protection:	A chemical resistant apron and/o product.	or protecti	ve cloth	ing are reo	commende	ed when ha	andling	or using	l this	
		9. PHYSICA					DTIES				
9.1	Appearance:					RUPE	RIIES				
9.2	Odor:	Liquid dispersion Solvent odor									
0.3	Odor Threshold:	NA									
.4	pH:	NA									
.5	Melting Point/Freezing Point:	NA									
.6	Initial Boiling Point/Boiling	138 °C (280.4 °F)									
.7	Range: Flashpoint:	, ,									
.7 .8	Upper/Lower Flammability	- 20 °C (- 4 °F) est.									
	Limits:	NA									
.9	Vapor Pressure:	NA									
.10	Vapor Density:	NA									
.11	Relative Density:	0.90									
.12	Solubility:	NA									
.13	Partition Coefficient (log P _{ow}):	NA									
.14	Autoignition Temperature:	NA									
.15	Decomposition Temperature:	NA									
.16	Viscosity:	NA									
.17	Other Information:	Evaporation rate slower than eth	er. VOC	regulate	ory: 6.73 lb	/gal (806	gr/ltr). VO	C actua	l: 6.43 l	b/gal (7	71 gr/ltr).
		10. ST	ABILI	TY &	REAC	τινιτγ	/				
	Stability:	Stable under normal conditions;	unstable	with hea	at or conta	mination.					
	Hazardous Decomposition	Oxides of carbon (CO, CO ₂), peroxides, irritating vapors.									
				maning	vuporo.						
0.2	Products: Hazardous Polymerization:	Will not occur.		incaring	vaporo.						
10.1 10.2 10.3 10.4	Products:	(,		0	•	nd direct s	unlight.				

Page 4 of 6 BTI-093

SDS Revision: 1.2 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 6/10/2019 **11. TOXICOLOGICAL INFORMATION** Routes of Entry Inhalation: YES Absorption: YES Ingestion: YES 11.1 112 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Acetone: LD₅₀ (oral, rat) = 5,800 mg/kg; LD₅₀ (oral, mouse) = 3 mg/kg; LC₅₀ (inh-6h, rat) = 50,100 ppm; Xylene: LD₅₀ (oral, rat) 4,300 mg/kg 11.3 Acute Toxicity See Section 4.4 Chronic Toxicity: 114 See Section 4.5 Toluene and Xylene: IARC Group 3 (not classifiable as to its carcinogenicity to humans). 11.5 Suspected Carcinogen: 11.6 Reproductive Toxicity: Toluene is reported to cause reproductive effects in humans Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: Toluene is reported to cause reproductive effects in humans Irritancy of Product: See Section 4.3 11.7 Biological Exposure Indices: 11.8 NE 11.9 Physician Treat symptomatically. Recommendations 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: The manufacturer has not reported any detailed studies on the environmental fate of this product. Toxicological data is available for some components in this mixture but all have not been provided in this safety data sheet. However, prudent practice dictates that the material should not be allowed to enter the environment. Ecotoxicity component information: Toluene: LC₅₀ (daphnia, 24h) = 313 mg/L; (blue gill fish, 24h) = 17 mg/L; (blue gill fish, 96h) = 13 mg/L; (fathead minnow fish, 24h) = 56 mg/L; fathead minnow, 96h)=34 mg/L; (goldfish) = 56.8 ppm. Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/L. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. 12.2 Effects on Plants & Animals There are no specific data available for this product 12.3 Effects on Aquatic Life NA 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler. 13.2 Special Considerations: U.S. EPA Hazardous Waste Number D001 (Ignitability). **14. TRANSPORTATION INFORMATION** The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR 14.1 49 CFR (GND): NOT REGULATED PER 49 CFR 173.150(f)(2) – NON-BULK PKG VOL ≤ 119 U.S. GLS (119 L) UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 5.0 L) 14.2 IATA (AIR): ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) Alb. $\widehat{\mathbf{Y}}$ $\mathbf{\widehat{\mathbf{Y}}}$ UN1263, PAINT, 3, II (LTD QTY, IP VOL \leq 0.5 L) IMDG (OCN): 14.3 UN1263, PAINT, 3, II (LTD QTY, IP VOL \leq 5.0 L) 14.4 TDGR (Canadian GND): UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 5.0 L) 14.5 ADR/RID (EU): UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 5.0 L) 14.6 SCT (MEXICO) UN1263, PINTURA, 3, II (CANT. LTDA., IP VOL ≤ 5.0 L) ADGR (AUS) 14.7 UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 5.0 L) EXCEPTED QUANTITY This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 14.8 500 mL per Outer Package) 15. REGULATORY INFORMATION SARA Reporting This product contains Toluene and Xylene, substances subject to SARA Title III, Section 313 reporting requirements. 15.1 Requirements SARA 304 (40 CFR Table 302.4) -Ethyl Acetate. This product contains Acetone, a substance subject to SARA Title III, Section 302 reporting requirements. 15.2 SARA Threshold Planning NA Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory.

Page 5 of 6 BTI-093

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.2 SDS Revision Date: 6/10/2019 15. REGULATORY INFORMATION – cont'd CERCLA Reportable 15.4 Ethyl Acetate: 2,270 kg (5,000 lbs); Xylene: 454 kg (1,000 lbs); Toluene: 454 kg (1,000 lbs); Acetone: 2,270 kg (5,000 lbs) Quantity (RQ): 15.5 Other Federal Requirements: Toluene is listed as a Hazardous Air Pollutant (HAP). This material does not contain any Class 1 Ozone depletors. This material does not contain any Class 2 Ozone depletors. Toluene is listed as a Hazardous substance under the CWA. Toluene is listed as a Priority Pollutant under the Clean water Act. Toluene is listed as a Toxic Pollutant under the Clean Water Act. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class D1, D2B (Materials Causing Immediate and Serious Toxic Effects, Other Toxic Effects). 15.7 State Regulatory Ethyl Acetate is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, WA, and Wisconsin Hazardous Information: Substances List (WI). Xylene is found on the following state criteria list: FL, MA, MI, MN, NJ, PA, WA and WI. Toluene is found on the following state criteria lists: CA65, FL, MA, MN, PA, WA, and WI Acetone is listed on the following state criteria lists: FL, MA NJ, PA, WA, and WI. Ethanol is found on the following state criteria lists: MA, MN, PA, and WA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: WARNING: This product can expose you to chemicals including Xylene and/or Toluene, which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov. **16. OTHER INFORMATION** DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE 16.1 Other Information: DROWSINESS OR DIZZINESS. CAUSES SKIN IRRITATION. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion proof equipment. Use non-sparking tools. Take action to prevent static discharges. Do not get in eyes, on skin, or on clothing. Avoid breathing dust/fume/mist/vapor/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/eyewear/protective clothing. IF ON SKIN: Gently wash with plenty of soap and water. Specific treatment - see supplemental first aid instructions in section 4 of this Safety Data Sheet). Take off contaminated clothing and wash it before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persist: Get medical advice/attention. In case of fire: Use CO₂, Halon (if permitted), Dry Chemical, Foam, as authorized to extinguish. Store in a well ventilated place. Keep cool. P405 - Store locked up. KEEP OUT OF REACH OF CHILDREN. WARNING: This product can expose you to chemicals including Xylene and/or Toluene, which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov. Terms & Definitions: 16.2 See last page of this Safety Data Sheet. 16.3 Disclaimer This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Birchwood Technologies' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: **Birchwood Technologies** 7900 Fuller Road **BIRCHWOOD** Eden Prairie, MN 55344 USA Tel: +1 (952) 937-7900 TECHNOLOGIES Fax: +1 (952) 937-7979 http://www.birchwoodtechnologies.com 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 ShipMate Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 Training & Consulting http://www.shipmate.com

Page 6 of 6 BTI-093

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.2

SDS Revision Date: 6/10/2019

DEFINITION OF TERMS

L

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists	
IDLH	Immediately Dangerous to Life and Health	
NOHSC	NOHSC National Occupational Health and Safety Commission (Australia)	
OSHA	U.S. Occupational Safety and Health Administration	
PEL	Permissible Exposure Limit	
STEL	Short Term Exposure Limit	
TLV	Threshold Limit Value	
TWA	Time Weighted Average	

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

	0	Minimal Hazard	HEALTH
	1	Slight Hazard	FLAMMABILITY
	2	Moderate Hazard	PHYSICAL HAZARDS
ſ	3	Severe Hazard	PERSONAL PROTECTION
	4	Extreme Hazard	

PERSONAL PROTECTION RATINGS:

		enen namee.		
Α	8		G 🕞 🌘	
в	8		н 🗐 🌘	
С	8		I 🕞 🌘	
D			J 📵 🕻	
Е	8		к 💮 🌘	
F	0		X Consult your special hand	supervisor or SOPs for ing directions.
Sa	afety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
	Boots	Protective Apron	Protective Clothing & Full Suit	Dust Respirator
Full	Face Respirator	Dust & Vapor Half- Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity – Repeat Exposure
STOT SE	Specific Target Organ Toxicity – Single Exposure

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	FLAMMABILITY LIMITS IN AIR:					
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	
ACD	Acidic	
ALK	Alkaline	
COR	Corrosive	
W	Use No Water	
ОХ	Oxidizer	
TREFOIL	Radioactive	



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{lo} , LD _{lo} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution
PNOR	Particulates Not Otherwise Regulated

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System	
DOT	U.S. Department of Transportation	
TC	Transport Canada	
EPA	EPA U.S. Environmental Protection Agency	
DSL	Canadian Domestic Substance List	
NDSL	Canadian Non-Domestic Substance List	
PSL	PSL Canadian Priority Substances List	
TSCA	U.S. Toxic Substance Control Act	
EU	EU European Union (European Union Directive 67/548/EEC)	
WGK	Wassergefährdungsklassen (German Water Hazard Class)	

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

\bigcirc	۲	٢		Ē	۲		Ĩ
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond	A CARLON OF CARLON				
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment