

SAFETY DATA SHEET



Page 1 of 6
BTI-095

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 6/10/2019

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	CLEARLOK[®] U2
1.2	Chemical Name:	Urethane blend
1.3	Synonyms:	861240, 861250
1.4	Trade Names:	Clearlok [®] U2
1.5	Product Use:	Sealant
1.6	Distributor's Name:	Birchwood Laboratories LLC
1.7	Distributor's Address:	7900 Fuller Road, Eden Prairie, MN 55344 USA
1.8	Emergency Phone:	ChemTrec +1 (800) 424-9300 / +1 (703) 527-3887 or Poison Control Center +1 (855) 281-1742
1.9	Business Phone / Fax:	+1 (952) 937-7900 / +1 (952) 937-7979

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a hazardous substance but not as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).</p> <p>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. CAUSES SKIN IRRITATION.</p> <p>Classification: Flam. Liq. 2, Skin Irrit. 2A, STOT SE 3, Skin Irrit. 2</p>	
2.2	Label Elements:	<p>Hazard Statements (H): H225 – Highly flammable liquid and vapor. H319 – Causes serious eye irritation. H336 – May cause drowsiness or dizziness. H315 – Causes skin irritation.</p> <p>Precautionary Statements (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 – Keep container tightly closed. P240 – Ground and bond container and receiving equipment. P241 – Use explosion proof equipment. P242 – Use non-sparking tools. P243 – Take action to prevent static discharges. P262 - Do not get in eyes, on skin, or on clothing. P261 – Avoid breathing dust/fume/mist/vapor/spray. P264 - Wash skin thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 – Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/eyewear/protective clothing. P302+P352 - IF ON SKIN: Gently wash with plenty of soap and water. P321 - Specific treatment - see supplemental first aid instructions in section 4 of this Safety Data Sheet). P362+p364 – Take off contaminated clothing and wash it before reuse. P303+P361+P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 – Call a POISON CENTER/doctor if you feel unwell. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P370+P378 – In case of fire: Use CO₂, Halon (if permitted), Dry Chemical, Foam, as authorized to extinguish. P403+P235 – Store in a well ventilated place. Keep cool. P405 – Store locked up. P501 - Dispose of contents/ container to an approved waste disposal plant.</p>	
2.3	Other Warnings:	<p> WARNING: This product can expose you to chemicals including Xylene, and/or Ethylbenzene, which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.</p> <p>KEEP OUT OF REACH OF CHILDREN. If medical advice is needed, have product container or label at hand.</p>	

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	TLV	STEL	IDLH		
PROPRIETARY INGREDIENTS	NA	NA	NA	60-90	NA	NA	NF	NF	NF	NA	NA	NA		
BUTYL ACETATE	123-86-4	AF7350000	204-658-1	10-20	150	200	150	200	NF	200	200	1700	150	
	Flam. Liq. 3; STOT SE 3; H226, H336													
XYLENE	1330-20-7	ZE2100000	215-535-7	5-10	100	150	(80)	350	NF	100	150	900		
	Flam. Liq. 3, Acute Tox. Oral 4, Skin Irrit. 2, Acute Tox. Dermal 4; H226, H312, H315, H332													
ETHYL BENZENE	100-41-4	DA0700000	202-849-4	1-5	100	150	100	434	543	100	150	800		
	Flam. Liq. 2; Acute Tox. 4 *; H225, H332													

SAFETY DATA SHEET

Page 2 of 6
BTI-095

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards


SDS Revision: 1.1

SDS Revision Date: 6/10/2019

4. FIRST AID MEASURES

4.1	First Aid:	<p><u>Ingestion:</u> DO NOT INDUCE VOMITING. Contact ChemTrec +1 (800) 424-9300 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.</p> <p><u>Eyes:</u> If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.</p> <p><u>Skin:</u> Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.</p> <p><u>Inhalation:</u> Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention.</p>													
4.2	Effects of Exposure:	<p><u>Ingestion:</u> If product is swallowed, may cause gastrointestinal disturbance.</p> <p><u>Eyes:</u> Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p><u>Inhalation:</u> Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.</p>													
4.3	Symptoms of Overexposure:	<p><u>Ingestion:</u> If product is swallowed, may cause gastrointestinal disturbance.</p> <p><u>Eyes:</u> Exposure to dust may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><u>Skin:</u> May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p><u>Inhalation:</u> Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.</p>													
4.4	Acute Health Effects:	Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of dust can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.													
4.5	Chronic Health Effects:	Non-irritating when used as directed. Possible allergic dermatitis in some sensitive individuals.													
4.6	Target Organs:	Eyes, Skin													
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions.	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #0000FF; color: white; text-align: center;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: #FF0000; color: white; text-align: center;">FLAMMABILITY</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="background-color: #FFA500; text-align: center;">PHYSICAL HAZARDS</td> <td style="text-align: center;">1</td> </tr> <tr> <td colspan="2" style="text-align: center;">PROTECTIVE EQUIPMENT</td> </tr> <tr> <td style="text-align: center;">EYES</td> <td style="text-align: center;">SKIN</td> </tr> <tr> <td style="text-align: center;">LUNGS</td> <td></td> </tr> </table>	HEALTH	2	FLAMMABILITY	3	PHYSICAL HAZARDS	1	PROTECTIVE EQUIPMENT		EYES	SKIN	LUNGS	
HEALTH	2														
FLAMMABILITY	3														
PHYSICAL HAZARDS	1														
PROTECTIVE EQUIPMENT															
EYES	SKIN														
LUNGS															
4.8	Notes to Physician:	Symptoms of poisoning may even occur after several hours; therefore, medical observation for at least 48 hours after the accident.													

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	<p>WARNING! FLAMMABLE LIQUID AND VAPOR! Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges.</p>	
5.2	Extinguishing Methods:	CO ₂ , Halon (if permitted), Dry Chemical, Foam, as authorized.	
5.3	Firefighting Procedures:	<p>This product is a Class IIIB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.</p> <p>First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.</p>	

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). Use safety glasses or safety goggles and face shield; use gloves and other protective clothing (e.g., apron, boots, etc.) to prevent skin contact.</p> <p><u>Small Spills:</u> Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible, inert material such as vermiculite or sand to soak up the product and place into a container for later disposal.</p> <p><u>Large Spills:</u> Keep incompatible materials (e.g., strong acids, alkalis, oxidizers) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Recover as much free liquid as possible and collect in acid-resistant container. Use absorbent to pick up residue. Avoid discharging liquid directly into a sewer or surface waters.</p>
-----	---------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET





Page 3 of 6
BTI-095

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 6/10/2019

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid breathing mists or spray. Avoid eye and skin contact. Wear protective equipment when handling product. Keep out of the reach of children. Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Do not expose to heat and flame. Use only in ventilated areas. Immediately clean-up and decontaminate any spills or residues. KEEP OUT OF THE REACH OF CHILDREN.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Keep containers covered when not in use. Store at temperatures at or below 25 °C (77 °F). Keep away from incompatible substances (see Section 10). Protect containers from physical damage.
7.3	Special Precautions:	Empty containers may retain hazardous product residues.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)	ACGIH		NOHSC			OSHA			OTHER	
		TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
		CHEMICAL NAME(S)									
		BUTYL ACETATE		150	200	150	200	NF	200	200	1700
		XYLENE		100	150	(80)	350	NF	100	150	900
		ETHYL BENZENE		100	150	100	434	543	100	150	800
8.2	Ventilation & Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).									
8.3	Respiratory Protection:	In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 									
8.4	Eye Protection:	Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended. 									
8.5	Hand Protection:	Wear protective, chemical-resistant gloves (e.g., neoprene) when using or handling this product. 									
8.6	Body Protection:	A chemical resistant apron and/or protective clothing are recommended when handling or using this product. 									

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Liquid dispersion
9.2	Odor:	Solvent odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	138 °C (280.4 °F)
9.7	Flashpoint:	- 20 °C (- 4 °F) est.
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	NA
9.11	Relative Density:	0.90
9.12	Solubility:	NA
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	Evaporation rate slower than Ether. VOC regulatory: 6.73 lb/gal (806 gr/ltr). VOC actual: 6.43 lb/gal (771 gr/ltr).

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under normal conditions; unstable with heat or contamination.
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO ₂), peroxides, irritating vapors.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks, high heat, incompatible substances and direct sunlight.
10.5	Incompatible Substances:	Avoid extreme heat and ignition sources. Oxidizing agents, strong acids, strong bases

SAFETY DATA SHEET

Page 4 of 6
BTI-095

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 6/10/2019

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: <u>Acetone</u> : LD ₅₀ (oral, rat) = 5,800 mg/kg; LD ₅₀ (oral, mouse) = 3 mg/kg; LC ₅₀ (inh-6h, rat) = 50,100 ppm; <u>Xylene</u> : LD ₅₀ (oral, rat) 4,300 mg/kg.		
11.3	Acute Toxicity:	See Section 4.4		
11.4	Chronic Toxicity:	See Section 4.5		
11.5	Suspected Carcinogen:	This product contains <u>Xylene</u> , a Group 3 carcinogen by IARC. This product contains <u>Xylene</u> , not classified as a human carcinogen, ACGIH A4. This product contains <u>Ethylbenzene</u> , a Group 2B carcinogen by IARC.		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans. There is ample evidence that <u>Xylene</u> produces embryotoxicity and fetotoxicity in mice and rats, but <u>Xylene</u> is not considered teratogenic.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 4.3		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	This product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: <u>Butyl Acetate</u> : K _{OC} = 1.82. Water solubility: 120 parts H ₂ O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler.
13.2	Special Considerations:	U.S. EPA Waste Number: D001 (characteristic - ignitable)

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1866, RESIN SOLUTION, 3, III, (LTD QTY, IP ≤ 5.0 L) or CONSUMER COMMODITY, ORM-D – until 01/01/2021	
14.2	IATA (AIR):	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 1.0 L) UN1866, RESIN SOLUTION, 3, III (LTD QTY, IP ≤ 1.0 L)	
14.3	IMDG (OCN):	UN1866, RESIN SOLUTION, 3, III, (LTD QTY, IP VOL ≤ 5.0 L)	
14.4	TDGR (Canadian GND):	UN1866, RESIN SOLUTION, 3, III, (LTD QTY, IP VOL ≤ 5.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 5.0 L)	
14.5	ADR/RID (EU):	UN1866, RESIN SOLUTION, 3, III, (LTD QTY, IP VOL ≤ 5.0 L)	
14.6	SCT (MEXICO):	UN1866, SOLUCIONES DE RESINA, 3, III, (CANTIDAD LIMITADA, IP VOL ≤ 5.0 L)	
14.7	ADGR (AUS):	UN1866, RESIN SOLUTION, 3, III, (LTD QTY, IP VOL ≤ 5.0 L)	
14.8	EXCEPTED QUANTITY	This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package)	

15. REGULATORY INFORMATION



15.1	SARA Reporting Requirements:	T This product contains <u>Xylene</u> and <u>Ethylbenzene</u> , substances subject to SARA Title III, Section 313 reporting requirements. SARA 304 (40 CFR Table 302.4) – <u>Ethyl Acetate</u> .
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
15.4	CERCLA Reportable Quantity (RQ):	<u>Ethyl Acetate</u> : 2,270 kg (5,000 lbs); <u>Xylene</u> : 454 kg (1,000 lbs); <u>Ethylbenzene</u> : 454 kg (1,000 lbs.)

SAFETY DATA SHEET


Page 5 of 6
BTI-095

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 6/10/2019

15. REGULATORY INFORMATION – cont'd

15.5	Other Federal Requirements:	This material does not contain any Class 1 Ozone depleters. This material does not contain any Class 2 Ozone depleters.	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class D1, D2B (Materials Causing Immediate and Serious Toxic Effects, Other Toxic Effects).	
15.7	State Regulatory Information:	<p><u>Ethyl Acetate</u> is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, WA, and Wisconsin Hazardous Substances List (WI).</p> <p><u>Xylene</u> is found on the following state criteria list: FL, MA, MI, MN, NJ, PA, WA and WI.</p> <p><u>Ethylbenzene</u> is found on the following state criteria list: CA, FL, MA, MN, PA and WA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>	
15.8	Other Requirements:	<p> WARNING: This product can expose you to chemicals including Xylene and/or Ethylbenzene, which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.</p>	

16. OTHER INFORMATION

16.1	Other Information:	<p>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. CAUSES SKIN IRRITATION. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion proof equipment. Use non-sparking tools. Take action to prevent static discharges. Do not get in eyes, on skin, or on clothing. Avoid breathing dust/fume/mist/vapor/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/eyewear/protective clothing. IF ON SKIN: Gently wash with plenty of soap and water. Specific treatment - see supplemental first aid instructions in section 4 of this Safety Data Sheet). Take off contaminated clothing and wash it before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO₂, Halon (if permitted), Dry Chemical, Foam, as authorized to extinguish. Store in a well ventilated place. Keep cool. P405 – Store locked up.</p> <p>KEEP OUT OF REACH OF CHILDREN.</p> <p> WARNING: This product can expose you to chemicals including Xylene and/or Ethylbenzene, which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Birchwood Technologies' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	<p>Birchwood Technologies 7900 Fuller Road Eden Prairie, MN 55344 USA Tel: +1 (952) 937-7900 Fax: +1 (952) 937-7979 http://www.birchwoodtechnologies.com</p>	
16.5	Prepared by:	<p>ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com</p>	

SAFETY DATA SHEET

Page 6 of 6
BTI-095

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 6/10/2019

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Protective Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity – Repeat Exposure
STOT SE	Specific Target Organ Toxicity – Single Exposure

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:	
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive

TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₁₀	Lowest dose to cause a symptom
TCLO	Lowest concentration to cause a symptom
TD₁₀, LD₁₀, & LD₅₀ or TC, TC₁₀, LC₁₀, & LC₅₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution
PNOR	Particulates Not Otherwise Regulated

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment